

www.esdan.com.au

Phone: +61 3 8791 7900 Fax: +61 3 9794 7660 Email: *info@esdan.com.au*

ESDAN PR CLEAR VINYL TUBE PINK PETROL RESISTANT TUBING

Esdan high grade clear pink tint PRCVT tubes are suitable for conveying most liquids including dilute acids and alkalies as well as low pressure gases. It is also resistant to oil and most petrochemicals.

Esdan Pink PRCVT tube is also highly flexible, light in weight, corrosion and abrasion resistant, whilst its clearness allows any blockages to be easily detected.





- Petrol resistant
- Corrosion & abrasion resistant
- Light weight
- Translucent Pink for easy identification
- Capable of carrying dilute acids
- Temperature range: -0°c to +50°c
- Oil resistant
- Capable of carrying most alkalies

PRODUCT CODE	I.D mm	O.D mm	WORKING PRESSURE	MIN. I

PRODUCT CODE	I.D mm	O.D mm	WORKING PRESSURE @23℃	MIN. BURST PRESSURE @23°C	COIL LENGTH	SPOOL LENGTH	REEL LENGTH
11-0305RD**	3	5	116 PSI	3.2 MPa	30m	50m	M.T.O
11-0508RD**	5	8	101 PSI	2.8 MPa	30m	50m	M.T.O
11-0609RD**	6	9	87 PSI	2.4 MPa	30m	50m	M.T.O
11-0811RD**	8	11	72 PSI	2.0 MPa	30m	50m	M.T.O
11-1013RD**	10	13	58 PSI	1.6 MPa	30m	50m	M.T.O
11-1215RD**	12.5	15.5	58 PSI	1.6 MPa	30m	50m	M.T.O

Esdan Plastics Pty. Ltd. 525—527 Hammond Road Dandenong South Victoria 3175 Australia

Disclaimer

While every reasonable care has been taken in preparation of this brochure, Esdan Plastics does not warrant that the information contained herein is without errors or omissions or suitable for your specific purpose. These specifications are to be used as a guide only, and are subject to change without notification. All safety factors are 4:1 unless stated otherwise. All information contained herein is subject to copyright and cannot be used without prior consent by ESDAN PLASTICS Pty. Ltd.