

ESDAN RED SUPERFLEX[®] RUBBER ALLOY AIR TOOL HOSE

Esdan Superflex is a rubber alloy air hose specifically designed for air tools. It is an economical compressor hose for use with road drills. Ideally suited for Civil Engineering, plant hire and Local Authorities.

All the stringent requirements of AS 2554 Class B are met by the Esdan Superflex.



- All Australian made
- Construction — Lining: Rubber Alloy
Textile reinforced
Cover: Rubber Alloy
- Temperature range: -15°C to +50°C
- Conforms to AS 2554B

PRODUCT CODE	I.D mm	O.D mm	WORKING PRESSURE @23°C	MIN. BURST PRESSURE @23°C	COIL LENGTH	REEL LENGTH
38-06RD****	6.3mm	12.9mm	232 PSI	6.4 MPa	20m/100m	250m
38-08RD****	8mm	15mm	232 PSI	6.4 MPa	20m/100m	250m
38-10RD****	10mm	17.3mm	232 PSI	6.4 MPa	20m/100m	250m
38-12RD****	12.5mm	21.3mm	232 PSI	6.4 MPa	20m/100m	200m
38-16RD****	16mm	24.8mm	232 PSI	6.4 MPa	20m/100m	MTO
38-19RD****	19mm	28mm	232 PSI	6.4 MPa	20m/100m	MTO
38-25RD****	25mm	34.2mm	232 PSI	6.4 MPa	20m/100m	MTO
38-32RD****	32mm	41.8mm	130 PSI	3.6 MPa	MTO	MTO
38-40RD****	40mm	52.4mm	130 PSI	3.6 MPa	MTO	MTO
38-50RD****	50mm	62mm	130 PSI	3.6 MPa	MTO	MTO

Esdan Plastics Pty. Ltd.
525—527 Hammond Road
Dandenong South
Victoria 3175 Australia

Disclaimer

While every reasonable care has been taken in preparation of this brochure, Esdan Plastics does not warrant that the information contained herein is without errors or omissions or suitable for your specific purpose. These specifications are to be used as a guide only, and are subject to change without notification. All safety factors are 4:1 unless stated otherwise. All information contained herein is subject to copyright and cannot be used without prior consent by ESDAN PLASTICS Pty. Ltd.