

## www.esdan.com.au

Phone: +61 3 8791 7900 Fax: +61 3 9794 7660 Email: *info@esdan.com.au* 

## **ESDAN GREY SUCTION HOSE**HEAVY DUTY SUCTION / DELIVERY HOSE

Esdan grey Suction and Delivery hose is a general purpose strong, flexible & smooth plasticized PVC hose. Lightly corrugated on the outside, it is reinforced with a continuous high impact PVC helix. It is ideal for use in medium duty suction and delivery of water, salt water, light chemicals and liquids.

It is also suitable for use in agricultural and industrial applications and constructions.

Resistant to crushing. Abrasion and weather resistant.







- High impact PVC helix reinforcement
- Resistant to crushing & abrasion
- UV Stabilised & Weather resistant
- Smooth bore
- Excellent flow characteristics
- Temperature range: 0.5°c to +60°c
- Suitable for liquid, powder & granular materials

PRODUCT CODE	I.D mm	I.D imperial	O.D mm	MAXIMUM OPERATING	VACUUM RATING	COIL LENGTH	WEIGHT Kg/mt	BEND RADIUS
40-25GRSUC020C	25	1"	32	90 PSI	9	20m	0.40	140
40-32GRSUC020C	32	1 ¼ "	39	90 PSI	9	20m	0.60	160
40-38GRSUC020C	38	1 ½ ″	45	70 PSI	9	20m	0.68	190
40-51GRSUC020C	51	2"	59	70 PSI	9	20m	0.98	250
40-63GRSUC020C	63	2 ½ "	73	70 PSI	8	20m	1.40	315
40-76GRSUC020C	76	3"	87	70 PSI	8	20m	1.65	375
40-102GRSUC020C	102	4"	116	60 PSI	8	20m	2.60	500
40-127GRSUC020C	127	5″	142	60 PSI	8	20m	3.65	625
40-152GRSUC020C	152	6"	170	60 PSI	8	20m	5.10	850

Esdan Plastics Pty. Ltd. 525—527 Hammond Road Dandenong South Victoria 3175 Australia

## Disclaimer

While every reasonable care has been taken in preparation of this brochure, Esdan Plastics does not warrant that the information contained herein is without errors or omissions or suitable for your specific purpose. These specifications are to be used as a guide only, and are subject to change without notification. All safety factors are 4:1 unless stated otherwise. All information contained herein is subject to copyright and cannot be used without prior consent by ESDAN PLASTICS Pty. Ltd.